

# **BLEACHER COVERS**

3 Row · 5 Row · 10 Row



## Features & Benefits

- ☼ Sunguard Shade Cloth® provides up to 96% UV protection
- ☼ Breathable shade cloth lowers ambient temperatures up to 20 degrees
- Fade, rot and mildew resistant
- Engineered to meet applicable International Building Codes
- Wind rating up to 115 mph with cover; 185 mph without (note: covers must be removed when winds are forecasted greater than 90 mph)
- \$\times 80\% water repellent (note: waterproof fabric is available in limited colors)
- Holds up to 5 lbs. snow load, 10 lbs. live load
- Huge steel and fabric color selection
- ☼ In-House Engineering and Design Department
- Hot dip galvanizing available for marine environments
- Available in powder coat finish or galvanized finish
- ☼ Perfect for foul ball protection!



## **Applications**

- ☼ Baseball Fields
- ☼ Soccer Fields
- ☼ Softball Fields
- ☼ Football Fields
- Aquatic Sporting Events
- ☼ Tennis Seating Areas
- Any outdoor spectator seating area





- strong, vibrant, and durable. The high-density polyethylene fabric with UV additives is Raschel knitted to ensure stability and a consistent shade pattern.
- Thread: PTFE (polymer) thread used for stitching is guaranteed not to rot due to UV exposure or other environmental causes.
- Corners: Reinforced, heat-sealed with vinyl interfacing sewn between layers.
- Tensioning cable is galvanized steel; fasteners are commercial grade stainless steel.
- Modular Design: Structures are designed to be interconnected to form infinite lengths of shade.
- Quick & Easy Cover Removal:

  No special tools required. Just loosen the turnbuckles or u-clamps with a standard wrench and you're done!

## STRONGEST NON-PRORATED WARRANTY!

15 Years Fabric & 20 Years Steel

	Bleacher Length 15'	Capacity 30	Size (W x L x H) 10'x18'x8'	
3 ROW	21'	42	10'x24'x8'	
	27'	54	10'x30'x8'	
	Bleacher Length	Capacity	Size (W x L x H)	
	15'	50	12'x18'x9'	
5 ROW	21'	70	12'x24'x9'	
	27'	90	12'x30'x9'	
	Bleacher Length	Capacity	Size (W x L x H)	
	15'	100	22'x18'x12'	
10 ROW	21'	140	22'x24'x12'	
	27'	180	22'x30'x12'	

Custom sizes available to shade any other bleacher size!

#### Installation

- All structures must be installed per factory specification. Hardware provided includes stainless steel bolts, galvanized cable, turnbuckles and cable clamps. Apollo Sunguard does not supply anchor bolts.
- Structures are direct embedment or surface mount on new footers poured to specifications.
- Structures can also be surface mounted on existing concrete slab (minimum 4.5" thick). If installed on existing concrete, columns must be a minimum of one foot away from edge of concrete.
- Footers require rebar. Footing requirements vary according to structure size. Footers can be recessed. Typical footers: 2' x 2' x 2' x 6' x 6' x 3'.

## Fire Safety

All of our fabric passes the ASTM E-84 fire rating test as well as the NFPA 255 and NFPA-701, and is rated a Class 1 Material.

## Available in 19 Vibrant Colors!

