

# BREEZEBRELLA® Offset SquareBrella



## Features & Benefits

- ☼ Sunguard Shade Cloth® provides up to 96% UV protection
- Breathable shade cloth lowers ambient temperatures up to 20 degrees
- Fade, rot and mildew resistant
- 🔅 Engineered to meet applicable International Building Codes
- Wind rating up to 115 mph with cover; 185 mph without cover (note: covers must be removed when winds are forecasted greater than 90 mph)
- 30% water repellent (note: waterproof fabric is available in limited colors)
- Holds up to 5 lbs. snow load, 10 lbs. live load
- Huge steel and fabric color selection
- ☼ In-House Engineering and Design Department
- ☼ Hot dip galvanizing available for marine environments
- Fixed center column design eliminates unnecessary perimeter posts that can become obstacles
- ☼ Offset column design also available
- All structures have a powder coat finish



## **Applications**

- ☼ Playgrounds
- ☼ Sandboxes
- ☼ Outdoor Dining
- ☼ Picnic Tables
- ☼ Pool Decks
- And much more!

# **Why Choose Carolina Shade Sails?**



- Fabric: Sunguard Shade Cloth® is strong, vibrant, and durable. The high-density polyethylene fabric with UV additives is Raschel knitted to ensure stability and a consistent shade pattern.
- Corners: Reinforced, heat-sealed with vinyl interfacing sewn between layers.

- ☼ Cable & Fasteners:
  - Tensioning cable is galvanized steel; fasteners are commercial grade stainless steel.
- Modular Design: Structures are designed to be interconnected to form infinite lengths of shade.
- Quick & Easy Cover Removal:
  No special tools required. Just loosen the turnbuckles or u-clamps with a standard wrench and you're done!

# STRONGEST NON-PRORATED WARRANTY!

15 Years Fabric & 20 Years Steel

Minimum Size Maximum Size

# Offset SquareBrella

10' x 10'

15' x 15'



4-Sided

Standard entry height: 8'-12' - Can be designed higher upon request.

#### Installation

- All structures must be installed per factory specification. Hardware provided includes stainless steel bolts, galvanized cable, turnbuckles and u-clamps. *Apollo Sunguard does not supply j-bolts or anchor bolts.*
- Structures are direct embedment or surface mount on new footers poured to specifications.
- Structures can also be surface mounted on existing concrete slab (minimum 4.5" thick). If installed on existing concrete, columns must be a minimum of one foot away from edge of concrete.
- Available in powder coat finish only.

## Fire Safety

All of our fabric passes the ASTM E-84 fire rating test as well as the NFPA 255 and NFPA-701, and is rated a Class 1 Material.

### Available in 19 Vibrant Colors!

