# Carolina Shade Sails

# **PLAYBRELLAS** Attached · Integrated Shade





#### Features & Benefits

- ☆ Sunguard Shade Cloth<sup>®</sup> provides up to 96% UV protection
- Breathable shade cloth lowers ambient temperatures up to 20 degrees
- $\ensuremath{\mathfrak{T}}$  Fade, rot and mildew resistant
- $\Leftrightarrow$  Engineered to meet applicable International Building Codes
- Wind rating up to 115 mph with cover; 185 mph without cover (*note:* covers must be removed when winds are forecasted greater than 90 mph)
- \* 80% water repellent (note: waterproof fabric is available in limited colors)
- $\ensuremath{\textcircled{\circ}}$  Holds up to 5 lbs. snow load, 10 lbs. live load
- $\Leftrightarrow$  Huge steel and fabric color selection
- In-House Engineering and Design Department
- $\ensuremath{\textcircled{}^\circ}$  Hot dip galvanizing available for marine environments
- All steel has a powder coat finish– Custom colors available to match the existing playground
- Large playgrounds can be covered with continuous shade using multiple overlapping PlayTowers
- Utilizing existing or new playground equipment columns, PlayTowers integrate seamlessly– offering safe, obstacle-free shade directly over the heart of the playground

# Applications

Playgrounds (new and existing playground equipment)

### Why Choose Carolina Shade Sails?

- Fabric: Sunguard Shade Cloth<sup>®</sup> is strong, vibrant, and durable. The high-density polyethylene fabric with UV additives is Raschel knitted to ensure stability and a consistent shade pattern.
- Thread: PTFE (polymer) thread used for stitching is guaranteed not to rot due to UV exposure or other environmental causes.
- Corners: Reinforced, heat-sealed with vinyl interfacing sewn between layers.

Cable & Fasteners:

Tensioning cable is galvanized steel; fasteners are commercial grade stainless steel.

- Modular Design: Structures are designed to be interconnected to form infinite lengths of shade.
- Quick & Easy Cover Removal: No special tools required. Just loosen the turnbuckles or u-clamps with a standard wrench and you're done!

STRONGEST NON-PRORATED WARRANTY! 15 Years Fabric & 20 Years Steel



Minimum Diameter

**Maximum Diameter** 

#### PlayBrellas

12'

20'



1 Center Column

Please note: Height to be determined at the design phase. PlayBrellas must be 8' from highest deck or platform. Playground column diameter determines the size range that can be installed.

#### Installation

- All PlayTowers must be installed by an Apollo Sunguard Certified PlayTower Installer.
- PlayTowers roof must be 8' above the highest play surface.
- Retrofitting existing playgrounds: footer reinforcement required unless playground is embedded into concrete pad, typically used at PIP foundation. Footing requirements vary according to structure size.
- Available in powder coat finish only. Custom powder coat colors available to match playground equipment.
- PlayTowers can only be integrated with steel column playgrounds ranging from 3.5" 11 gauge to 6" 11 gauge.
- Aluminum, plastic, or wood playground posts will need to be replaced with steel columns to utilize PlayTowers or PlayBrellas.

# Fire Safety

All of our fabric passes the ASTM E-84 fire rating test as well as the NFPA 255 and NFPA-701, and is rated a Class 1 Material.

# Available in 19 Vibrant Colors!

