

PLAYTOWERS

Attached · Integrated Shade







Features & Benefits

- Sunguard Shade Cloth® provides up to 96% UV protection
- ☼ Breathable shade cloth lowers ambient temperatures up to 20 degrees
- Fade, rot and mildew resistant
- 🔅 Engineered to meet applicable International Building Codes
- ☼ Wind rating up to 115 mph with cover; 185 mph without cover (note: covers must be removed when winds are forecasted greater than 90 mph)
- ☼ 80% water repellent (note: waterproof fabric is available in limited colors)
- Holds up to 5 lbs. snow load, 10 lbs. live load
- Huge steel and fabric color selection
- ☼ In-House Engineering and Design Department
- Hot dip galvanizing available for marine environments
- All steel has a powder coat finish— Custom colors available to match the existing playground
- Large playgrounds can be covered with continuous shade using multiple overlapping PlayTowers
- Utilizing existing or new playground equipment columns, PlayTowers integrate seamlessly– offering safe, obstacle-free shade directly over the heart of the playground

Applications

Playgrounds — new and existing playground equipment

Why Choose Carolina Shade Sails?

- Fabric: Sunguard Shade Cloth™ is strong, vibrant, and durable. The high- density polyethylene fabric with UV additives is Raschel knitted to ensure stability and a con-sistent shade pattern.
- Thread: PTFE (polymer) thread used for stitching is guaranteed not to rot due to UV exposure or other environmental causes.
- Corners: Reinforced, heat-sealed with vinyl interfacing sewn between layers.

- Cable & Fasteners:
 - Tensioning cable is galvanized steel; fasteners are commercial grade stainless steel.
- Modular Design: Structures are designed to be interconnected to form infinite lengths of shade.
- Quick & Easy Cover Removal: No special tools required. Just loosen the turnbuckles or u-clamps with a standard wrench and you're done!

STRONGEST NON-PRORATED WARRANTY!

15 Years Fabric & 20 Years Steel

PlayTowers
4 Columns/6 Columns

14' x 14'

24' x 30'



Please note:

- Height will be determined at the design phase
- Playground column diameter determines the size range that can be installed.

Installation

- All PlayTowers must be installed by an Apollo Sunguard Certified PlayTower Installer.
- ☼ PlayTowers roof must be 8' above the highest play surface.
- Retrofitting existing playgrounds: footer reinforcement required unless playground is embedded into concrete pad, typically used at PIP foundation. Footing requirements vary according to structure size.
- Available in powder coat finish only. Custom powder coat colors available to match playground equipment.
- PlayTowers can only be integrated with steel column playgrounds ranging from 3.5" 11 gauge to 6" 11 gauge.
- Aluminum, plastic, or wood playground posts will need to be replaced with steel columns to utilize PlayTowers or PlayBrellas.

Fire Safety

All of our fabric passes the ASTM E-84 fire rating test as well as the NFPA 255 and NFPA-701, and is rated a Class 1 Material.

Available in 19 Vibrant Colors!

